

## Up To 24.000" O.D. (609.6 mm)

## Versatile, Reliable

The H&S Tool RS24 reciprocating saw is a versatile, reliable tool that can cut up to 24.000" (609.6 mm) diameter. It is used as a hand held tool on small diameter applications. For larger diameters, a variety of clamping devices, saw blades and accessories enable cutting tubes, pipes and even structural steel. An optional automatic feed for hands-free operation is also available.

The powerful, reliable 1.5 h.p. (1.1 kW) pneumatic motor cycles up to 330 strokes per minute. The blades are made of high quality steel and are quickly and easily replaced for maximum cutting efficiency.

The bow option (shown on pipe) provides stability and increases accuracy. Small and large bows are offered. They limit maximum pipe size in a single set up to the "A" dimension.

A Small	13.000"	(330.2 mm)
A Large	21.000"	(533.4 mm)
В	30.000"	(762.0 mm)
C Small	20.000"	(508.0 mm)
C Large	26.000"	(660.4 mm)

## Specifications\*

Working Range	Up to 24.000" (609.6 mm) O.D.
Pneumatic Motor	1.5 H.P. (1.1 kW)
Recommended Air Pressure	
Recommended Volume	
Strokes per Minute	
Length of Stroke	2.375" (60.3 mm)
Length (Base Plate to Tail)	
Weight, Motor Only	15.0 lbs. (6.8 kg)

С



P.O. Box 393 Wadsworth, OH 44282, U.S.A. Tel: +1-330-336-4550 Fax: +1-330-336-9159 email: info@hstool.com Web Sites: hstool.com & multiprep.com

## • Excellent Power-To-Weight Ratio

:52

- Safe, Reliable
  Pneumatic Power
- Cuts Pipes And Structural Steel Materials
- 24.000" (609.6 mm) Maximum Diameter Working Range
- Optional Automatic Feed
- Many Blade Sizes
  And Accessories



\*Specifications are subject to change without notice.

© 2010. All rights reserved. Form No. RSWS-06 Printed in U.S.A.